

FireFix

FEAR NO FIRE

FIRE EXTINGUISHER

PRODUCT CATALOG



COMPLETE FIRE PROTECTION

TESTED & CERTIFIED FIRE EXTINGUISHERS

Our fire extinguishers performances have been tested and certified by Jakarta Fire Department with registration number

LAB-DAMKAR-DKI-NO 11/LHU/I/2020



PORTABLE FIRE EXTINGUISHERS



DRY POWDER

Dry powder is highly versatile fire fighting agent for A, B, C & D fire classes and suitable for most risk. In addition, to deal with electrical hazards, flammable liquids, gasses and metals, it also effective for vehicle fires.



Wood, Paper
Textile, Fabric



Petrol, Diesel
Oils



Electrical



Magnesium, Titanium
Potassium

TYPE

FP-1

FP-2

FP-3

FP-3.5

FP-4

FP-4.5

FP-5

FP-6

FP-9



AFFF FOAM

Spray-foam extinguisher is suitable for both A & B fire classes. It works by covering fire and eliminate contact between fire and oxygen. It will cool down fire and prevents the fire starts to burn again. In addition, it also prevents explosions on the fire's spot.



Wood, Paper
Textile, Fabric



Petrol, Diesel
Oils

TYPE

FFO-6

FFO-9



CO2

Carbon dioxide agent is suitable for fire that caused by electrical equipments or B fire class. The carbon dioxide agent also recognized for its non-damage, highly effective performance and cleanliness.



Petrol, Diesel
Oils



Electrical

TYPE

FC-2.2

FC-3

FC-5

FC-6.8



HFC-125

HFC-125 is a clean agent and known as the world's most eco friendly extinguisher. It is actually a substitute for halon fire extinguisher. HFC-125 is suitable for A, B, and C fire classes. It's a safe agent for fire that caused by electrical appliance since the agent itself is not a conductor and does not leave residues.



Wood, Paper
Textile, Fabric



Petrol, Diesel
Oils



Electrical



Magnesium, Titanium
Potassium

TYPE

FH-1

FH-2

FH-3

FH-3.5

FH-4

FH-4.5

FH-5

FH-6

FH-9

TROLLEY FIRE EXTINGUISHERS

POWDER TROLLEY

Trolley dry powder fire extinguisher is best for places that required large amount of fire extinguishers' agent. Featured stainless steel cylinder, ultra-high UV powder coated with red-painted finishing and galvanised powder coated red trolley.



Wood, Paper
Textile, Fabric



Petrol, Diesel
Oils



Electrical



Magnesium, Titanium
Potassium

TYPE

FPT-20

FPT-25

FPT-50

AFFF FOAM TROLLEY

GuardALL's 25 litre and 50 litre AFFF Foam mobile extinguishers are best suited for A and B fire classes. They have a stainless steel cylinder, ultra-high UV powder coated with red-painted finishing and galvanised red coated trolley.



Wood, Paper
Textile, Fabric



Petrol, Diesel
Oils

TYPE

FFOT-25

FFOT-50

CO2 TROLLEY

Trolley carbon dioxide fire extinguisher is characterized by their high performance for fires involving electrical risk like computers, office equipments, generators and etc. Its non-conductive, clean and safe agent, ensuring minimal damage to electrical equipments and furnishings.



Petrol, Diesel
Oils



Electrical

TYPE

FCOT-25

DRY POWDER

TYPE	FP-1	FP-2	FP-3	FP-3.5	FP-4	FP-4.5	FP-5	FP-6	FP-9
Height (cm)	31	42	46	47.5	47.5	50	50	55.5	60
Width (cm)	10.5	19.5	24	22	22	24	24	24	24
Diameter (cm)	8.5	10.7	12.5	12.8	12.8	14.5	14.5	14.5	17
Capacity (kg)	1	2	3	3.5	4	4.5	5	6	9
Weight full (kg)	1.6	3.3	4.5	5	5.5	6.8	7.3	8.5	12.5
Weight empty (kg)	0.6	1.3	1.5	1.5	1.5	2.3	2.3	2.5	3.5
Discharge time (sec)	11	13	14	15	18	21	21	24	39
Discharge range (m)	3 to 12	3 to 12	3 to 12	3 to 12	3 to 12	3 to 12	3 to 12	3 to 12	3 to 12
Test pressure (bar)	25	25	25	25	25	25	25	25	25
Working pressure at 20°C (bar)	15	15	15	15	15	15	15	15	15
Minimum effective discharge (%)	±95	±95	±95	±95	±95	±95	±95	±95	±95
Temperature range (°C)	-20 to 60	-20 to 60	-20 to 60	-20 to 60	-20 to 60	-20 to 60	-20 to 60	-20 to 60	-20 to 60
Fire rating	1A : 2B	2A : 4B	3A : 6B	3A : 6B	4A : 8B	4A : 8B	5A : 10B	5A : 12B	7A : 15B
Special feature	Firecek App Integration								

AFFF FOAM

TYPE	FFO-6	FFO-9
Height (cm)	55.5	60
Width (cm)	24	24
Diameter (cm)	14.5	17
Capacity (kg)	6	9
Weight full (kg)	8.5	12.5
Weight empty (kg)	2.5	3.5
Discharge time (sec)	27	29
Discharge range (m)	3 to 12	3 to 12
Test pressure (bar)	25	25
Working pressure at 20°C (bar)	15	15
Minimum effective discharge (%)	90	90
Temperature range (°C)	0 to 60	0 to 60
Fire rating	N/A	N/A
Special feature	Firecek App Integration	

CO₂

TYPE	FC-2.2	FC-3	FC-5	FC-6.8
Height (cm)	50	70.5	77.5	97.5
Width (cm)	18	18	29.5	29.5
Diameter (cm)	11	11	14.5	14.5
Capacity (kg)	2.2	3	5	6.8
Weight full (kg)	7.1	11.1	16.8	20.3
Weight empty (kg)	4.9	8.1	11.8	13.5
Discharge time (sec)	8	10	18	23
Discharge range (m)	3 to 12	3 to 12	3 to 12	3 to 12
Test pressure (bar)	200	200	200	200
Working pressure at 20°C (bar)	56	56	56	56
Minimum effective discharge (%)	90	90	90	90
Temperature range (°C)	-20 to 60	-20 to 60	-20 to 60	-20 to 60
Fire rating	1B	2B	3B	4B
Special feature	Firecek App Integration			

HFC-125

TYPE	FH-1	FH-2	FH-3	FH-3.5	FH-4	FH-4.5	FH-5	FH-6	FH-9
Height (cm)	31	42	46	47.5	47.5	50	50	55.5	60
Width (cm)	10.5	19.5	24	22	22	24	24	24	24
Diameter (cm)	8.5	10.7	12.5	12.8	12.8	14.5	14.5	14.5	17
Capacity (kg)	1	2	3	3.5	4	4.5	5	6	9
Weight full (kg)	1.6	3.3	4.5	5	5.5	6.8	7.3	8.5	12.5
Weight empty (kg)	0.6	1.3	1.5	1.5	1.5	2.3	2.3	2.5	3.5
Discharge time (sec)	11	13	14	15	18	21	21	24	39
Discharge range (m)	3 to 12	3 to 12	3 to 12	3 to 12	3 to 12	3 to 12	3 to 12	3 to 12	3 to 12
Test pressure (bar)	25	25	25	25	25	25	25	25	25
Working pressure at 20°C (bar)	15	15	15	15	15	15	15	15	15
Minimum effective discharge (%)	±95	±95	±95	±95	±95	±95	±95	±95	±95
Temperature range (°C)	-20 to 60	-20 to 60	-20 to 60	-20 to 60	-20 to 60	-20 to 60	-20 to 60	-20 to 60	-20 to 60
Fire rating	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Special feature	Firecek App Integration								

POWDER TROLLEY

TYPE	FPT-20	FPT-25	FPT-50
Fire Class	A, B, C, D	A, B, C, D	A, B, C, D
Extinguisher Agent	Dry Powder	Dry Powder	Dry Powder
Capacity (kg)	20	25	50
Temperature Range (°C)	-20 to 60	-20 to 60	-20 to 60
Working Pressure at 20°C (bar)	15	15	15
Special Feature	Firexek App Integration		

AFFF FOAM TROLLEY

TYPE	FFOT-25	FFOT-50
Fire Class	A, B	A, B
Extinguisher Agent	Dry Powder	Dry Powder
Capacity (kg)	25	50
Temperature Range (°C)	-20 to 60	-20 to 60
Working Pressure at 20°C (bar)	15	15
Special Feature	Firexek App Integration	

CO₂ TROLLEY

TYPE	FCOT-25
Fire Class	B, C
Extinguisher Agent	CO ₂
Capacity (kg)	25
Temperature Range (°C)	-20 to 60
Working Pressure at 20°C (bar)	25
Special Feature	Firexek App Integration

THERMATIC FIRE EXTINGUISHER

For Automatic Protection



THERMATIC FIRE EXTINGUISHERS



HFC-125

Thermatic fire extinguisher is a fire protection device that works automatically based on the temperature. When, the room's temperature where the thermatic fire extinguisher is installed hits a certain point, the bulb will break and let the media spread through the tip to stop fire.



Wood, Paper
Textile, Fabric



Petrol, Diesel
Oils



Electrical



Magnesium,
Titanium Potassium

TYPE

FHTH-5

TYPE	FHTH-5
Height	328 mm
Width	278 mm
Capacity	5 kg
Fire Class	A, B, C, D
Extinguisher Agent	HFC-125
Protection Range	±8,5 m² at 25°C to 30°C
Working Pressure	125 Psi
Detector temperature	68°C
Special Feature	Firecek App Integration



RISK FREE 5 YEARS GUARANTEE

- Verified by Jakarta Fire Department
- Free Fire Extinguishers Checking Application

GET FIRE  CEK APP
YOUR FIRE ASSISTANT!

FIREFIX POWERED BY FIRECEK APP

Leave fire extinguisher tags and turn to Firecek App, the solution for checking your fire extinguishers. Easy, safe and fast. Firecek makes it easy for you to manage all your fire extinguishers, wherever and whenever with excellent services from our special team.

Our products are equipped with a Firecek QR code. So, you just need to scan the QR code using your smartphone and save it to the Firecek's inventory feature.



THE BENEFITS

- Unlimited storage
- More than 1000 fire extinguishers in one account
- Handled by Special Team
- We work with the best fire protection vendors in your city
- Full control
- You got full access to manage your stuffs

*T&C: Optional by customer request and service coverage availability.

THE FIRST FIRE EXTINGUISHERS CHECKING APPLICATION IN THE WORLD



Download FIRECEK
Free Now!